

509, 260

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
2 October 2003 (02.10.2003)


PCT

(10) International Publication Number  
**WO 03/080256 A1**

- (51) International Patent Classification<sup>7</sup>: **B05B 7/28**
- (21) International Application Number: PCT/AU03/00375
- (22) International Filing Date: 26 March 2003 (26.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
PS 1347 26 March 2002 (26.03.2002) AU  
27244/2003 4 February 2003 (04.02.2003) JP
- (71) Applicant (for all designated States except US): **SPATER SHIELD (AUST) PTY LTD** [AU/AU]; 21 Capelli Road, Wingfield, South Australia 5013 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **VAVRA, Antonin** [AU/AU]; 10 Baru Street, Pooraka, South Australia 5095 (AU).
- (54) Agent: **PHILLIPS ORMONDE & FITZPATRICK**; 367 Collins Street, Melbourne, Victoria 3000 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: CONTROL DEVICE FOR DISPERSING A LIQUID IN A FLUID



(57) Abstract: The invention is directed to a control device for use with dispersion apparatus capable of dispersing a liquid in a fluid, such as a gas, to form a mist. The dispersion apparatus includes a chamber having a liquid-containing portion and a mist-containing portion. The control device includes a fluid inlet in communication with a fluid outlet, the fluid outlet being such that, in use, it is within the liquid-containing portion of the chamber. The control device also includes a mist outlet capable of being, in use, in communication with the mist-containing portion of the chamber. The fluid outlet includes means for controlling the flow of fluid therefrom such that, in use, either the degree of turbulence or the ratio of fluid to liquid in the mist can be controlled. The control device may also include a by-pass means between the fluid inlet and the mist outlet for assisting in controlling the ratio of liquid to fluid in the mist.

WO 03/080256 A1

WO 03/080256 A1



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*